

Ipe Oil™

Hardwood Deck Finish

Ipe Oil™ Hardwood Deck Finish, by DeckWise®, is an oil based product that protects and conditions woods such as Ipe and Ma-hogany while also maintaining a natural appearance. It has been produced with professional results in mind, providing exceptional penetration, water repellency and U.V. protection.

SHAKE, STIR & MIX WELL • Questions/Comments: www.DeckWise.com

SURFACE PREPARATION & APPLICATION

It is recommended to sand new wood decking with 80-120 grit sandpaper prior to applying Ipe Oil™ Hardwood Finish to open the wood's pores and allow natural oils to come to the surface. Always clean older gray or dirty wood decking before applying Ipe Oil™ Hardwood Finish. Use a product like DeckWise® Part 1 Wood Cleaner and DeckWise Part 2 Wood

Brightener to clean hardwood decks. Allow wood decking to completely dry for at least 24 to 48 hours. Previously stained or treated wood should be sufficiently weathered to allow for complete penetration of Ipe Oil™ Hardwood Finish. New wood should be aged at least 6-8 weeks and cleaned before applying product.

Ipe Oil™ Hardwood Deck Finish is an oil-based natural wood finish specifically designed for use on exterior hardwood decks. Ipe Oil™ Hardwood Deck Finish provides excellent penetration of even the densest hardwoods with minimal raising of the grain. It protects and conditions the wood while maintaining a completely natural appearance. Ipe Oil™ Hardwood Deck Finish may be used on exterior hardwood to enhance the wood's natural beauty with exceptional results on Ipe, Tigerwood, Cumaru and other exotic hardwoods.

Application Directions - Step by step instructions for a beautiful hardwood deck.



**STEP 1
PREP**

Make sure surface is clean, dry & in good condition. Clean the deck surface thoroughly to make sure it is totally free of debris or foreign residue of any kind. Also, remove previous stain or paint completely before applying Ipe Oil™ Hardwood Deck Finish. Apply when temperatures are between 40-95°F and surface is not hot to the touch. Do not thin.



**STEP 2
MIX**

Stir well initially and during use. Inter-mix all containers of the same color to ensure uniform appearance. Cover plants, grass and concrete to protect from spills.



**STEP 3
TEST**

Apply to a small test area of Ipe Oil™ Hardwood Deck Finish to ensure complete penetration and color satisfaction before proceeding with the entire project.



**STEP 4
EQUIP**

Recommended Method:
Roll on decking with a 3/8" nap paint roller.

Alternative Methods:
Apply with a quality bristle brush, pad, or cloth rag.



**STEP 5
APPLY**

Apply a uniform even coat. Stain the full length of boards, keeping a wet edge. One coat is sufficient for most applications. Thoroughly wipe down all boards with a rag within 5 minutes. This will prevent tackiness and a surface sheen.



**STEP 6
CLEAN**

Immediately clean application equipment with mineral spirits (paint thinner).



DISPOSAL

DO NOT leave rags balled up or application materials unattended; properly dispose of immediately. Lay rags flat to dry, out of the sun and heat.

See Warnings on label regarding safe waste disposal.

Product Applications

- Hardwood Decks
- All Exterior Wood Surfaces
- Fences
- Wood Railings

Features

- Special formula for Ipe, Tigerwood, Cumaru and other hardwoods
- Contains Transoxide pigments for added grain enhancement
- Long lasting water repellency
- Low odor

Drying Time

Temperature, wood and humidity all effect drying time. Allow 24 hours in most applications.

Approximate Coverage per Gallon*

Smooth Wood: 200-300 sq ft / gallon
Rough Wood: 150-250 sq ft / gallon
*Coverage on dense hardwoods

WARNING: Do not leave rags in a pile, they will self-combust or catch fire. Rags, brushes, rollers, steel wool or waste soaked with Ipe Oil™ Hardwood Deck Finish may also spontaneously catch fire if improperly discarded. Immediately after each use, place waste materials in a sealed, water-filled metal container. Dispose of empty cans or unused portion in accordance with local, state, and federal regulations.

Decks

Horizontal surfaces collect airborne dust, dirt and tree pollen which accelerate graying (weathering). Decks should be cleaned once in the Spring and once in the Fall to assure natural wood appearance. Decks should be treated with Ipe Oil™ Hardwood Deck Finish no more than once a year. Excess oil product not absorbed within 5 minutes must be thoroughly removed to prevent tackiness and surface sheen. For further information please visit our website at www.DeckWise.com.

Conditions of Sale

In lieu of all warranties, expressed or implied, the manufacturer and sellers only obligation shall be to replace such quantity of Ipe Oil™ Hardwood Deck Finish as is proven to be defective as per www.IpeOil.com/warranty.

Seller and manufacturer shall not be liable for loss or damage connected with the use and/or handling of this product. User should determine suitability of this product for the intended use before applying it. User assumes all risk and liability in connection therewith.

CONTAINS PETROLEUM DISTILLATE

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: If swallowed, do not induce vomiting. Call Physician immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

VOC COMPLIANT:
Less than 250 grams per liter



UN1263

VEHICLE TYPE:

Solvent based, blend of natural oils and synthetic alkyds. Low VOC formula MHV contains VOC exempt solvent.

PACKAGING:

One U.S. gallon / 3.785 Liters

SOLIDS BY VOLUME: 49%

COVERAGE:

Rough Wood: 150 to 250 square feet per gallon
Smooth Wood: 200 to 300 square feet per gallon

DRY TIME:

Allow 24 hours in good drying conditions

SOLIDS BY WEIGHT: 48%

COLORS:

Available in Natural

APPLY WITH:

Brush, roller, airless spray

VOC CONTENT: < 250 g/L (as supplied)

WEIGHT PER GALLON:

8.2 Pounds

VISCOSITY:

15-18 Seconds Zahn #2 at 77F



DeckWise® • The Ipe Clip® Fastener Company, LLC • 2111 58th Ave. East, Bradenton, FL 34203
Phone: 941-896-9851 • Email: info@DeckWise.com • Web: www.DeckWise.com